WEVER & DUCRÉ
LIGHTING

BLAS
2.0

736287B4

Project

Type

Notes

Quantity

Date

GENERAL
Ceiling
Surface
Jet Black
IP65
Exterior
840 lm
9005 [a]

LED
3000 K
CRI 80
L70 / 50000 h
3-step binning

OPTICAL
Jut-Out


PHYSICAL
Length 130 mm
Width 130 mm
Height 79 mm
1.3 kg

ELECTRICAL
phase-cut dim
220 - 240 V
Total connected power 9.4 W
PC1
Safety distance 0.3 m


[a] RAL Palette colors may deviate slightly due to production conditions.







LIGHT DISTRIBUTION



['736287B4'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.

December 15, 2020

© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

WEVER & DUCRÉ
LIGHTING

BLAS
2.0

736287B4

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.89	0.83	0.78	0.73
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF[a]	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF[a]	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

[a] According to “CIE 97, Maintenance of indoor electric lighting systems”, 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

['736287B4'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com