Galileo

Emanuele Ricci, 2023

LUMINA

Suspension lamp providing direct and diffused light. The glass diffuser consists of 6 sheets of 15 mm thick extra-clear float glass, glued together, milled, ground and polished to a perfect quality shape. The mount housing the customized integrated LED is machined from aluminum billet using a CNC machine. The mount is finished in brushed nickel or brushed gold.

FINISHINGS

Brushed Nickel
3000K - cod. GALD44K30
2700K - cod. GALD44K27
ON/OFF-PUSH DIM-1/10V DALI
Ceiling rose: Brushed Nickel/Black

Brushed Gold
3000K - cod. GALD45K30
2700K - cod. GALD45K27
ON/OFF-PUSH DIM-1/10V DALI
Ceiling rose: Brushed Gold/Black

Brushed Nickel
3000K - cod. GALTF44K30220
2700K - cod. GALTF44K27220
PHASE CUT
Ceiling rose: Brushed Nickel/Black

Brushed Gold
3000K - cod. GALTF45K30220
2700K - cod. GALTF45K27220
PHASE CUT
Ceiling rose: Brushed Gold/Black

LIGHT EMISSION

Light source power: 12W
Power absorption: 18W
Light Emission: Diffuse
Light Direction: Directional
Light Source: COB LED
Source Flux 3000K: 1400lm@350mA
Emitted Flux 3000K: 692 lm
Efficacy 3000K: 45 lm/W
Source Flux 2700K: 1360lm@350mA
Emitted Flux 2700K: 641 lm
Efficacy 2700K: 43 lm/W
CCT: 2700/3000K
CRI: 97
Lifetime: >55000h

ELECTRICAL FACTS

Stand-by absorption: < 0,5
Mains Voltage: 100-264VAC
Master output: 350mA
Ta max: 40°C

PACKAGING DATA

Box dimensions: 29,5x28,7x26,8cm
Volume: 0,023 m^3
Gross weight: 5 kg





