
Occhio

Sento lettura
datasheet

LED floor luminaire, connection via power supply unit (converter) with wall plug. Modular LED head-body-system allows free combination of different surfaces of head, body and base. Removable head for configuration and maintenance purposes, LED changeable. Heads available with one sided or double sided light output, power of light source 18 W.

Lighting effect changeable by using optional inserts, dichroic color filters can be added. Adjustment via heat-decoupled carbon pin (fixation of head against rotation optional). Switch- and dimmable via »touchless control« with gestures at the head.





dimensions in mm


technical data Sento lettura


properties	material	aluminium, steel chrome-plated, painted or anodised, plastic, glass, optical plastic	
	length	1250 / 1600 mm	
	rotation head	360°	
	swivel range	1250 mm; max. 18° / 1600 mm; max. 12°	
	weight	8.5 kg	
surface	head	matt gold, rose gold, bronze, shiny chrome, matt chrome, glossy white, matt white, matt black	
	body	matt white, matt black, shiny chrome, matt chrome	
	base	shiny chrome, glossy white, matt chrome, matt white, matt black	
	cable	matt white, matt black, transparent	
Occhio LED	average life time	> 50.000 hrs	
	energy efficiency class	A + / A	
	power	18 W	
	color rendering index	perfect color; CRI Ra 97	high flux; CRI Ra 85
	color temperature	2700, 3000 K	3000, 3500, 4000 K
	recommended use	residential and public	public
electricity	dimming	»touchless control« and Occhio air (optional)	
	power supply plug unit	with integrated converter, cable length 180 cm, for use with 230 V AC	
	permitted operating conditions	max. 30°C for indoor use only	

IP20

Sento lettura
lighting effects

head single sided






Sento B

diffuse light

insert: diffusor glass

luminous flux:			
	perfect color	18 W	1000 lm
	high flux	18 W	1370 lm







Sento C

directed light
beam angle approx. 80°

insert: lens

luminous flux:			
	perfect color	18 W	1140 lm
	high flux	18 W	1570 lm







Sento S 40

directed light
beam angle approx. 40°

insert: spot lens, lens
soft edge glass

luminous flux:			
	perfect color	18 W	1130 lm
	high flux	18 W	1560 lm





Sento S 30


directed light
beam angle approx. 30°


insert: spot lens, lens
fresnel lens

luminous flux:			
	perfect color	18 W	1110 lm
	high flux	18 W	1530 lm

Sento lettura
lighting effects

head double sided







Sento A

diffuse light in both directions

insert:	diffusor glass		
	diffusor glass		
luminous flux:	perfect color	18 W	1090 lm
	high flux	18 W	1500 lm






Sento D

directed light in both directions
beam angle approx. 80°

insert:	lens		
	lens		
luminous flux:	perfect color	18 W	1270 lm
	high flux	18 W	1750 lm





Sento E

diffuse up light
directed down light
beam angle approx. 80°

insert:	diffusor glass		
	lens		
luminous flux:	perfect color	18 W	1170 lm
	high flux	18 W	1620 lm