

116 (4.5")

PENDANTS: one

MOUNTING: deep brushed nickel canopy 116mm (4.5") in diameter x

40mm (1.6") deep

LAMPING: 1.5w LED or 20w xenon

COAX: adjustable. 3000mm (10') standard / up to 30500mm

(100') maximum

MATERIALS: porcelain, borosilicate glass, braided metal coaxial cable,

electrical components, brushed nickel canopy

WEIGHT: approximately 0.5kg (1.1lb)

POWER SUPPLIES integral.

DESCRIPTION

The deep canopy is a single 21 pendant fixture with a deep brushed nickel canopy. The canopy is 116mm (4.5") in diameter and 40mm (1.6") deep. It is designed for surface mounted applications that cannot make use of a junction box or ceiling cavity. The canopy is completely enclosed by a backplate, which houses the transformer. The pendant drop lengths on this light fixture are adjustable up to the specified maximum.

Inspired by the sporadic, discordant arrangement of barnacles on a rock surface, the 21 is fabricated from thin sheets of porcelain wrapped around a trumpet shaped borosilicate diffuser. Each diffuser houses a low voltage lamp. A strong contrast is established between the organically distributed soft light passing through the white porcelain skin and the sharp, crisp light passing through the borosilicate glass diffuser.

NOTES

- + Purchase replacement lamps online at www.bocci.ca/shop/bulbs
- + Unless otherwise noted when ordering, all chandeliers will be outfitted to be xenon compatible.

US patent # US D556,361 Worldwide patents issued and pending.





Made in Vancouver, Canada


Vancouver Berlin


sales@bocci.ca europe@bocci.ca www.bocci.ca www.bocci.ca


DEEP CANOPY


approx 0.5kg (1.1lb)


















1

Very carefully uncoil the braided coaxial cable in a spool like manner. Insert your index fingers into opposite sides of the roll then rotate your fingers around each other to unroll the coaxial cable.

Use patience: allow the cable to uncoil completely to avoid kinks.

2

Determine the overall drop for the pendant fixture.

Thread the coaxial cable through the canopy, use a 2mm Allen key to loosen the setscrew in the canopy and gently feed the cable through until you have reached your desired drop length.

3

Use Allen key to tighten the setscrew to hold the strain relief and secure the coaxial cable at its new length. Perform a gentle tug test to ensure it is secure.

DO NOT OVERTIGHTEN.

Note: The strain relief is a black plastic collar around the coaxial cable. There is a single slot opening on the side of the strain relief component. It is essential that this opening is oriented at 90 degrees to set screw chamber. There can be no contact between the set screw and the cable.

RISK OF ELECTRIC SHORT!

4

Xenon (110V) or LED: connect the black wire to black and white wire to white wire.

Xenon (230V): connect black wire to brown wire and white wire to blue wire.

Connect the coaxial cable to the open slots in the terminal block on the 12V side of the power supplies.

For multiple pendant installations, ensure that the braided outer wires are all connected to one 12V output wire and all inner insulated wires are connected to the other or a short will occur.

Once all coaxial connections are made, lift the fixture into position and connect the line voltage to the open slot in the appropriate terminal block.

5

The client is responsible to ensure fasteners are attached to a robust structural substrate.

Tuck the power supply and wiring into the canopy. Line up the fastener holes or connect directly to structural ceiling surface using the fasteners provided.

Turn power to fixture on.

6

Bocci LED or xenon lamps are included. Lamping is transformer specific.

Plug the lamp into the socket.
Do not touch the lamp with
your bare hands. Ensure
power to lamp is working
correctly.

Thread the coaxial cable through the shade, followed by the borosilicate diffuser and finally slide on the retainer.

7

Clean fingerprints from surfaces.

For additional assistance, please contact Bocci:

Vancouver sales@bocci.ca

www.bocci.ca Berlin

europe@bocci.ca www.bocci.ca

US patent # US D556,361

Worldwide patents issued and pending.

Made in Vancouver. Canada







