




RINI SNEAK IP44

CEILING RECESSED



1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.18 kg | IP44 | 0.3-D | 36°

76-79 | 46 | 4-25

	CODE
	154261W_
	154261B_


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	470/630	>90	3
3000K	500/680	>90	5
1800-2850K 16V 290/390		>95	9

ALWAYS USE


power supply | 500mA

	CODE
10W	90214405
15W dim	90224501
20W DALI	90244602

350mA power supplies on page 694



only for LED version



1.0 MR16

QR-CBC51 max. 12W | GU5.3
12V | excl. power supply
aluminium powder coated

0.12 kg | IP44 | 0.3-D

76-79 | 55 | 4-25


	CODE
	154210W0
	154210B0

ALWAYS USE

power supply | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

more specs on page 699



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.16 kg | IP44 | 0.3-D

76-79 | 80 | 4-25

	CODE
	154220W0
	154220B0

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 701