

### 1.0 LED

LED 7/10W | 350/500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.31kg IP20 3-0,3-D P 36°

76 90 4-30

|  | CODE     |
|--|----------|
|  | 112161W_ |
|  | 112161S_ |
|  | 112161B_ |

blade springs 78

|  | CODE      |
|--|-----------|
|  | 112161W_C |
|  | 112161B_C |

#### Light Colour Selection

|                                | LUMEN   CRI   | CODE |
|--------------------------------|---------------|------|
| 2700K                          | 520/710   >90 | 3    |
| 3000K                          | 540/740   >90 | 5    |
| 4000K                          | 580/790   >90 | 6    |
| 1800-2850K   16V 330/450   >95 |               | 9    |

#### ALWAYS USE

power supply

|                 | CODE     |
|-----------------|----------|
| 350mA   10W     | 90223401 |
| 500mA   10W     | 90214404 |
| 500mA   15W dim | 90224501 |

more power supplies on page 588



### 1.0 MR16

QR-CBC51 max.35W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.25kg IP20 3-0,9-D

76 90 4-30

|  | CODE     |
|--|----------|
|  | 112110W0 |
|  | 112110S0 |
|  | 112110B0 |

blade springs 78


|  | CODE      |
|--|-----------|
|  | 112110W0C |
|  | 112110B0C |

#### ALWAYS USE

power supply

|               | CODE     |
|---------------|----------|
| 12V   10W dim | 90221401 |
| 12V   25W dim | 90221701 |
| 12V   70W dim | 90221904 |

more specs on page 591



### 1.0 PAR16

PAR16 max.35W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.29kg IP20 3-0,9-D

76 105 4-30

|  | CODE     |
|--|----------|
|  | 112120W0 |
|  | 112120S0 |
|  | 112120B0 |

blade springs 78

|  | CODE      |
|--|-----------|
|  | 112120W0C |
|  | 112120B0C |

#### OPTIONAL

PAR16 LED GU10 7W  
phase-cut dim

|            | CODE     |
|------------|----------|
| 2700K      | 901228W2 |
| 3000K      | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 593

## DEEP CEILING RECESSED



p. 587