


La linea - 2,5mt

BIG - Bjarke Ingels Group



IP65   Dimmable: 



LUMINAIRE

- Watt: **15W/m**
- Flux Lumineux (lm): **960 lm/m**
- CCT: **3000K**
- Efficiency: **100%**
- Efficacy: **64lm/W**
- CRI: **95**
- Dimmable Typology: **APP,Push,Dali**

Remarques

5 wall/ceiling supports included

DESCRIPTION

La Linea is a basic principle that generates an open system and a comprehensive relation with space and humans. It turns light into an ideal fixture for outdoor spaces, architectures, parks, or public and urban areas to requalify common spaces, create social and engaging landscapes and promote relations between people and their surroundings.

It easily fits into indoor and outdoor spaces by leveraging on an unprecedented combination of factors, including quality of light, IP protection grade, flexibility, modularity.

BIG's idea is once again transposed, thanks to the know-how of Artemide, into a product that looks basic but it is rich of technological innovation.

Today, new installation possibilities make it an increasingly transversal solution. With an aluminum back bone is possible to suspend La Linea modules creating linear or curved geometries in custom composition.

With the new recessed accessories La Linea can be suspended from the extremities and can freely define the softly curving geometries during installation in the space.

CODE PRODUIT: T4601010

CARACTÉRISTIQUES

- Code Article : **T4601010**
- Couleur: **White**
- Installation: **PlafonnierApplique**
- Matériaux: **Silicone flexible tube**
- Séries: **Design Collection, 2021 Artemide Collection, Architectural Outdoor**
- Environnement: **Indoor**
- dessiné par: **BIG - Bjarke Ingels Group**

DIMENSIONS

- Longueur : **cm 250**
- Diamètre: **cm 4**

ACCESSOIRES

NO
IMAGE
AVAILABLE

Additional wall/ceiling support R304975

NO
IMAGE
AVAILABLE

Driver 120W - CV 220-240V - 24VDC - SELV -
Undimmable - IP20 DV1033

NO
IMAGE
AVAILABLE

Driver 90W - CV 100-240VAC - 24VDC - 0-10V -
IP65 DV1075

NO
IMAGE
AVAILABLE

Driver 90W - CV 110-240VAC - 24VDC - APP+PUSH
dim - IP20 DV1075APP

NO
IMAGE
AVAILABLE

Driver 90W - CV 100-240VAC - 24VDC - DALI dim -
IP65 DV1076

NO
IMAGE
AVAILABLE

Powerkit 96W - CV 110-240VAC - 24VDC - Non
Dimmerabile - IP65 A4681210

NO
IMAGE
AVAILABLE

Powerkit 96W - CV 110-240VAC - 24VDC - DALI/0-
10V/PUSH - IP20 A4681010

NO
IMAGE
AVAILABLE

Powerkit 96W - CV 110-240VAC - 24VDC - APP+PUSH
- IP20 A4681010APP

NO
IMAGE
AVAILABLE

Powerkit 96W - CV 110-240VAC - 24VDC -
APP+PUSH - IP65 T4681010APP