



WEVER & DUCRÉ  
LIGHTING

# FINLIN 1.0

370184B3

Project

Type

Notes

Quantity

Date

## GENERAL

Wall

Surface

Jet Black

IP20

Interior

350 lm

9005<sup>a</sup>

## LED

2700 K

3-step binning

## OPTICAL

Opal

## PHYSICAL

Diameter 9 mm

Height 623 mm

0.15 kg

## ELECTRICAL

incl. PS | phase-cut dim

220 - 240 V



Total connected power 6 W

LED Inset 6 W

PC2

Safety distance 0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.





WEVER & DUCRÉ  
LIGHTING

# FINLIN 1.0

370184B3

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.93	0.89	0.86	0.83
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.