



WEVER & DUCRÉ  
LIGHTING

# MILES 2.0 ROUND

317574WN3

Project \_\_\_\_\_

Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

## GENERAL

Wall \_\_\_\_\_

Surface \_\_\_\_\_

Walnut Wood \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

400 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

3-step binning \_\_\_\_\_

## PHYSICAL

Diameter 190 mm \_\_\_\_\_

Height 37 mm \_\_\_\_\_

0.77 kg \_\_\_\_\_

## ELECTRICAL


phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

Total connected power 11 W \_\_\_\_\_

PC2 \_\_\_\_\_

Safety distance 0.3 m \_\_\_\_\_





WEVER & DUCRÉ  
LIGHTING

# MILES 2.0 ROUND

317574WN3

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.84	0.8
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.