



WEVER & DUCRÉ
LIGHTING

RAY WALL OUTDOOR 4.0

741248W2

Project

Type

Notes

Quantity

Date

GENERAL

Wall

Surface

Signal White

IP65

Exterior

Total 400 lm

9003^a

LED

2700 K

CRI 80

L90 / 50000 h

3-step binning

PHYSICAL

Diameter 150 mm

Height 160 mm

0.53 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 5.5 W


PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.



IP65    0,3 m





WEVER & DUCRÉ
LIGHTING

RAY

WALL OUTDOOR 4.0

741248W2

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.95	0.93	0.9	0.9
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.