



WEVER & DUCRÉ
LIGHTING

RINI SNEAK 1.0 PAR16

154220B0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Jet Black

IP44

Interior

355^a, 385^b, 390^c lm

9005^d

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

L70 / 50000 h

OPTICAL

Wide Flood

Beam angle 48°

PHYSICAL

Diameter 84 mm

Height 99 mm

0.16 kg

ELECTRICAL

100 - 240 V

Total connected power 8.8^c, 8.9^b, 10^a

W

PC2

Safety distance 0.9 m

CUTOUT

Diameter 76-79 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 25 mm

Recessed depth 80 mm

^a LED 1800-2850K CRI 90 silver


^b LED 3000K CRI 80 white

^c LED 2700K CRI 80 white


^d RAL Palette colors may deviate slightly due to production conditions.



IP44



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

RINI

SNEAK 1.0 PAR16

154220B0

CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	499	0.89
2	125	1.78
3	55	2.67
4	31	3.56
5	19	4.45

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	ø50·58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	ø50·58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	ø50·58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	ø50·58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	ø50·58	9 0 1 2 2 8 W 4

PAR16 LED Lamp | Ambient

TYPE	Ø·H (MM)	ORDERCODE
1800-2850K >90 CRI GU10	ø50·58	9 0 1 2 2 9 S 9