



WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 0.8

745162A5

Project
Type
Notes
Quantity
Date

GENERAL

Wall
Recessed
Anthracite Grey
IP65
Exterior
80 lm

LED

3000 K

ELECTRICAL

excl. power supply
24 V
LED Inset 3 W
Class 3
Safety distance 0.3 m

PHYSICAL


Length 80 mm
Width 30 mm
Height 80 mm
0.3 kg

CUTOUT

Length 66 mm
Width 66 mm
Min. ceiling thickness 12 mm
Recessed depth 40 mm



Square wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; degree of protection IP65; PC3; driver not included; light source not replaceable;





WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 0.8

745162A5

MOUNTING

Concrete Housing

L · W · H (MM)

69-69-61

ORDERCODE

9 0 0 1 2 0 4 6

Recessed Housing incl. plasterkit

L · W · H (MM)

110-110-64

ORDERCODE

9 0 0 1 2 0 4 7

ELECTRICAL

Driver

TYPE

L · W · H (MM)

ORDERCODE

35W | 24V | IP67

175-31-42,5

9 0 2 1 2 8 0 2

100W | 24V | IP67

178-68-39

9 0 2 1 2 9 0 3