



**WEVER & DUCRÉ**  
LIGHTING

# RETO OUTDOOR 1.3

745362A5

Project

Type

Notes

Quantity

Date

## GENERAL

Wall

Recessed

Anthracite Grey

IP65

Exterior

160 lm

## LED

3000 K

## ELECTRICAL

excl. power supply

24 V

LED Inset 5 W

Class 3

Safety distance 0.3 m

## PHYSICAL

Length 130 mm

Width 30 mm

Height 130 mm

0.4 kg

## CUTOUT

Length 115 mm


Width 117 mm

Min. ceiling thickness 12 mm

Recessed depth 40 mm



Square wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; degree of protection IP65; PC3; driver not included; light source not replaceable;





WEVER & DUCRÉ  
LIGHTING

# RETO OUTDOOR 1.3

745362A5

## MOUNTING

### Concrete Housing

TYPE	L · W · H (MM)	ORDERCODE
ORIS 1.3	120-55-120	9 0 0 1 2 0 4 0

### Recessed Housing incl. plasterkit

TYPE	L · W · H (MM)	ORDERCODE
ORIS 1.3	160-68-160	9 0 0 1 2 0 4 1

## ELECTRICAL

### Driver

TYPE	L · W · H (MM)	ORDERCODE
35W   24V   IP67	175-31-42,5	9 0 2 1 2 8 0 2
100W   24V   IP67	178-68-39	9 0 2 1 2 9 0 3