



WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 2.0

745262A5

Project

Type

Notes

Quantity

Date

GENERAL

Wall

Recessed

Anthracite Grey

IP65

Exterior

330 lm

LED

3000 K

ELECTRICAL

excl. power supply

24 V

LED Inset 7 W

Class 3

Safety distance 0.3 m

PHYSICAL

Length 200 mm

Width 30 mm

Height 80 mm

0.4 kg

CUTOUT

Length 47 mm


Width 182 mm

Min. ceiling thickness 12 mm

Recessed depth 40 mm



Rectangular wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; degree of protection IP65; PC3; driver not included; light source not replaceable;





WEVER & DUCRÉ
LIGHTING

RETO OUTDOOR 2.0

745262A5

MOUNTING

Concrete Housing

L · W · H (MM)

122 · 55 · 190

ORDERCODE

9 0 0 1 2 0 4 2

Recessed Housing incl. plasterkit

L · W · H (MM)

160 · 67 · 250

ORDERCODE

9 0 0 1 2 0 4 3

ELECTRICAL

Driver

TYPE

L · W · H (MM)

ORDERCODE

35W | 24V | IP67

175 · 31 · 42,5

9 0 2 1 2 8 0 2

100W | 24V | IP67

178 · 68 · 39

9 0 2 1 2 9 0 3